



US006594382B1

(12) **United States Patent**
Woodall

(10) Patent No.: **US 6,594,382 B1**
(45) Date of Patent: **Jul. 15, 2003**

(54) **NEURAL SENSORS**

(75) Inventor: **Roger L. Woodall, Jewett City, CT (US)**

(73) Assignee: **The United States of America as represented by the Secretary of the Navy, Washington, DC (US)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/436,956**

(22) Filed: **Nov. 4, 1999**

(51) Int. Cl.⁷ **G06K 9/62; G06F 15/18; G06G 7/00**

(52) U.S. Cl. **382/156; 382/159; 706/20**

(58) Field of Search **382/155, 156, 382/158, 159, 48, 226, 190, 157; 706/15, 16, 20, 22, 23, 41, 43, 52**

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,263,097 A * 11/1993 Katz et al. 382/48
5,524,065 A * 6/1996 Yagasaki 382/226
5,680,481 A * 10/1997 Prasad et al. 382/190

5,687,291 A * 11/1997 Smyth 395/10
5,842,194 A * 11/1998 Arbuckle 706/52
5,850,470 A * 12/1998 Kung et al. 382/157
6,038,338 A * 3/2000 Nguyen 382/159

* cited by examiner

Primary Examiner—Jon Chang

Assistant Examiner—Brian Le

(74) *Attorney, Agent, or Firm*—James M. Kasischke; Michael F. Oglo; Jean-Paul A. Nasser

(57) **ABSTRACT**

A neural sensor is provided which receives raw input data defining a pattern, such as image or sound data, and generates a classification identifier for the pattern. The neural sensor has a pattern array former which organizes the raw input data into the proper array format. A first order processing section receives the pattern array and generates a first order feature vector illustrative of first order features of the input data. A second order processing section also receives the pattern array and generates at least one second order feature vector illustrative of gradients in the input data. A vector fusion section receives the feature vectors from the first and second order processing sections and generates a single fused feature vector which is provided to a pattern classifier network. The pattern classifier network, in turn, generates a pattern classification for the input data.

16 Claims, 6 Drawing Sheets

